








REV.	ECN NO.	DESCRIPTION	DATE	DESIGN
A		调整电气性能描述&更新图框	2021.11.11	XUETAO GUO

NOTE:

- 1.MATERIAL: SEE BOM
- 2.FINISH: CONTACT: 50U"MIN,NICKEL UNDERPLATING OVERALL. SURFACE FOLLOW THE P/N.
3. SPEC. PLS. REFER TO EI064:
- 4.ORDERING INFORMATION:

BT0406 H- XX X X X
 WITHOUT "H" : WITH HALOGEN
 WITH "H" : HALOGEN FREE
 PIN NO. _____
 PACKING:
 0:TAPE&REEL
 1:TUBE

B: BLACK
 N: NATURAL



CKTs	A	B	C	D	E
30	8.30	5.60	3.60	6.00	7.16
50	12.30	9.60	7.60	10.00	11.16
80	18.30	15.60	13.60	16.00	17.16
100	22.30	19.60	17.60	20.00	21.16
120	26.30	23.60	21.60	24.00	25.16
N	B+2.7	(N/2-1)*0.4	B-2.0	B+0.4	B+1.56

2	TERMINAL	~	COPPER ALLOY
1	HOUSING	1	LCP ,UL94-V0
NO.	DESCRIPTION	Q'TY.	MATERIAL

一般公差
TOLERANCES
 X ±0.3 .XX ±0.15
 .X ±0.25 .XXX ±0.1
 ANGLES ±2°

檢驗尺寸標示
 SYMBOLS INDICATE CLASSIFICATION DIMENSION
 MARK IS CRITICAL DIM.
 MARK IS MAJOR DIM.

表面處理 (FINISH)

品名 (TITLE)
 0.4PITCH 1.5MH BTB FEMALE CONNECTOR

圖號 (DWG NO.)
 C-BT0406H-XXXXX

比例 (SCALE) 單位 (UNITS) 5:1 mm

製圖 (DR) XUETAO GUO
 審核 (CHKD) LEO-HE
 核准 (APPD) LEO-HE

張數 (SHEET) 1 OF 1
 尺寸 (SIZE) A4
 版次 (REV) A

RECOMMENDED PCB LAYOUT
 DEFAULT TOL: ±0.05